

SPECIFICATION CLAUSE



Full Fill Cavity Wall Top Panel CT/TP

The built-in full fill cavity wall Top Panel insulation shall be the Unilin Insulation CavityTherm CT/TP Full Fill Cavity-Wall Top Panel manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, including corner boards and ancillary detail components, comprising of a rigid Polyisocyanurate (PIR) core between composite foil facings with engineered HIPS outer skin. The Unilin Insulation CT/TP___mm with a Agrément declared Lambda value of 0.021 W/mK to achieve a U-Value of ___W/m²K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 150, F30 12. Uniclass Pr 25 71 63 66.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165:2012+A2:2016

Certification

- BBA Certification No. 23/7059
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

- **T** 0371 222 1033
- **F** 0371 222 1044
- E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

- T 04690 66000
- **F** 04690 66090
- E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Thin-R CT/TP Full Fill Cavity Wall Top Panel Insulation

Face Size

1200mm x 225mm

Edge Profile

Rebated on all four edges

Thickness

100mm / 110mm / 125mm / 150mm