



SPECIFICATION CLAUSE



WARM-R HD E GREY

The wall insulation shall be Unilin Insulation Warm-R HD E Grey manufactured to EN 13163:2012+A2:2016 by Unilin Insulation, comprising a graphite enhanced EPS __ __mm with a Agrément declared Lambda value of 0.031 W/mK to achieve a U-Value of __ __ W/m²K for the wall, floor or roof element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause E20 200, E20 30, J31 331. Uniclass Pr 25 71 63 26.

Insulation

Expanded Polystyrene

Standard

BS EN 13163:2012+A2:2016

Certification

- BBA Certification No. 24/7224
- NSAI Certification No. 04/0022
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire,
UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan,
Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Warm-R HD E Grey

Face Size

Various

Edge Profile

Square Edge

Thickness

30mm / 40mm / 50mm / 60mm / 80mm /
100mm / 120mm / 140mm / 160mm

Other sizes available dependent on quantity & lead time.