



# SPECIFICATION CLAUSE

## CAVITYTHERM BUILT IN FULL FILL WALL INSULATION

### Full Fill Cavity Walls

**CT/PIR**

The full fill cavity wall panel insulation shall be Unilin Insulation CavityTherm CT/PIR manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, comprising of a rigid Polyisocyanurate (PIR) core between composite foil facings with engineered HIPS outer skin. The CT/PIR \_\_\_mm to achieve a U-Value of \_\_\_W/m<sup>2</sup>K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 150, F30 12. Uniclass 25 71 63 66.

#### Insulation

Polyisocyanurate Rigid Foam

#### Standard

BS EN 13165:2012+A2:2016

#### Certification

- BBA Certification No. 23/7059
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033

**F** 0371 222 1044

**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000

**F** 04690 66090

**E** info.ui@unilin.com

unilininsulation.ie

#### Product Reference

Unilin Insulation CavityTherm CT/PIR  
Full Fill Cavity Wall Insulation

#### Face Size

1200mm x 450mm

#### Edge Profile

Rebated on all four edges

#### Thickness

100mm / 110mm / 125mm / 150mm