



SPECIFICATION CLAUSE

FLAT ROOF TOTAL FLAT ROOF SOLUTIONS

Partially Bonded Torched-on Built-up Bituminous Felt Systems

TR/BGM

The tapered roof insulation shall be Unilin Insulation Thin-R TR/BGM ___mm thick manufactured to EN 13165:2012+A2:2016 by Unilin Insulation comprising of a rigid Polyisocyanurate (PIR) core between fleece finished bitumen/glass fibre facings with a Agrément declared Lambda value as low as 0.024 W/mK. The tapered roof insulation shall be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause J41 420, J42 10, J42 430, J42 420, J41 10. Uniclass 25 71 63 66.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165:2012+A2:2016

Certification

- BBA Certification No. 24/7235
 - BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Thin-R TR/BGM
Tapered Roof Insulation

Face Size

1200mm x 1200mm

Other tapers available dependent on quantity & lead time.

Edge Profile

Square Edge

Thickness

30-50mm / 50-70mm / 70-90mm / 90-110mm