

SPECIFICATION CLAUSE

XTROLINER SUPERIOR PERFORMANCE PIR INSULATION*

Steel & Timber Frame Systems

XO/FB

The wall insulation shall be XtroLiner XO/FB manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, comprising of a rigid Polyisocyanurate (PIR) core between textured foil facings. The XtroLiner XO/FB_ _ _mm with a Agrément declared Lambda value of 0.021 W/mK to achieve a U-Value of _ _ _W/m²K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause K10 15, K10 205, B15 110, P10 40, P10 190. Uniclass Pr 25 71 63 66.

Insulation

Modified Polyisocyanurate Rigid Foam

Standard

BS EN 13165:2012+A2:2016

Certification

- BBA Certification No. 23/6874
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation XtroLiner XO/FB
Steel & Timber Frame Insulation

Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

Edge Profile

Square Edge

Thickness

50mm / 60mm / 75mm / 80mm / 100mm / 120mm

*The reference to superior performance relates to the product or ranges thermal conductivity or fire performance or a combination of both, when compared to our Thin-R range.