



# SPECIFICATION CLAUSE

## ACCESSORIES

### Wall Cavity Closer CLOSE-R

The partial/full fill cavity wall cavity closer insulation shall be Unilin Insulation Close-R manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, comprising of a rigid PVC-U Outer Profile with encapsulated rigid Polyisocyanurate (PIR) core between composite foil facings suitable for \_ \_ \_mm cavity. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 180, F30 18. Uniclass Pr 35 90 50 64.

#### Insulation

Polyisocyanurate Rigid Foam

#### Standard

BS EN 13165:2012+A2:2016

#### Certification

- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033  
**F** 0371 222 1044  
**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000  
**F** 04690 66090  
**E** info.ui@unilin.com

unilininsulation.ie

#### Product Reference

Unilin Insulation Closer-R Cavity Wall Closer  
Panel Insulation

#### Edge Profile

Square Edge